BMW M4 Competition Coupé. Specifications.

		BMW M4 Competition Coupé
Body		
No of doors/seats		2/4
Length/width/height (unladen)	mm	4794 / 1887 / 1393
Wheelbase	mm	2857
Track, front/rear	mm	1617 / 1605
Ground clearance	mm	120
Turning circle	m	12.2
Fuel tank capacity	approx. I	59
Engine oil	I	7.4
Weight, unladen, to DIN/EU	kg	1725 / 1800
Max load to DIN	kg	430
Max permissible weight	kg	2155
Max axle load, front/rear	kg	1075 / 1135
Max trailer load, braked	kg	
(12%)/unbraked		- -
Max roofload/max towbar download	kg	75 / –
Luggage comp capacity		440
Air resistance	c _d x A	0.34 x 2.29
Power Unit		
Config/No of cyls/valves		In-line / 6 / 4
Engine technology	(r	M TwinPower Turbo technology with two mono-scroll turbochargers, indirect charge air cooling, High Precision Injection naximum injection pressure: 350 bar), VALVETRONIC fully variable valve timing
		Double-VANOS variable camshaft timing
Effective capacity	CC	2993
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	9.3
Fuel		RON 98 (min. RON 91)
Max output	kW/hp	375 / 510
at	rpm	6250
Max torque	Nm	650
<u>at</u>	rpm	2750 – 5500
Electrical System		
Battery/installation	Ah/-	70 / luggage compartment
Driving Dynamics and Safe	ty	
Suspension, front		Adaptive M suspension with double-joint spring strut axle in lightweight
		aluminium construction, M-specific kinematics and elastokinematics
Suspension, rear		Adaptive M suspension with five-link axle in lightweight aluminium/steel construction, rear-axle subframe with rigid bolted connection to the body,
Dualiza frant		M-specific kinematics and elastokinematics
Brakes, front		M Compound brakes, vented, with six-piston fixed callipers
Brakes, rear Driving stability systems		M Compound brakes, vented, with single-piston floating callipers Standard: DSC incl. ABS, ASC and M Dynamic Mode (MDM), can be switched off, integrated wheel slip limitation, CBC (Cornering Brake Control), DBC
		(Dynamic Brake Control), Dry Braking function, Start-Off Assistant, Active M Differential,
Safety equipment	Ś	Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags front and rear, three-point inertia-reel seatbelts on all seats with belt stopper, belt tensioner and belt force limiter at the front, crash sensors, tyre pressure indicator
Steering	ı	Electric Power Steering (EPS) with M-specific Servotronic function and variable sport ratio
Steering ratio, overall	:1	15.0
Tyres, front/rear	.1	275/40 ZR18 103Y XL
		285/35 ZR19 103Y XL
Rims, front/rear		9.5J x 18 light-alloy 10.5J x 19 light-alloy

			BMW M4 Competition Coupé
Transmission			
Type of transmi	ssion		Eight-speed M Steptronic transmission with Drivelogic
Gear ratios	1	:1	5.000
		:1	3,200
		:1	2.143
	IV	:1	1.720
	V	:1	1.313
	VI	:1	1,000
	VII	:1	0.823
	VIII	:1	0.640
	R	:1	3.478
Final drive		:1	3.154
Performance			
Power-to-weigh	nt ratio (DIN)	kg/kW	4.6
Output per litre		kW/l	125.3
Acceleration	0-100 km/h	S	3.9
Acceleration	80-120 km/h		
in 4th/5th gear		S	2.6 / 3.4
Top speed		km/h	250 / 290 ²⁾
BMW Efficient			
BMW EfficientD	,		Brake Energy Regeneration, Electric Power Steering,
standard features			Auto Start Stop function, Optimum Shift Indicator in manual shift mode,
			BMW EfficientLightweight, on-demand operation of ancillary units, map-
			regulated oil pump, rear differential with optimised efficiency, Li-ion battery,
			optimised aerodynamic attributes
Fuel Consum	ntion FCF		
with standard ty			
Urban		I/100 km	14.6
Extra-urban		I/100 km	7.6
Combined		1/100 km	10.1-10.2
CO ₂		g/km	230-233
Emission rating		<u> </u>	Euro 6d

 $Specifications\ apply\ to\ ACEA\ markets/data\ relevant\ to\ homologation\ applies\ in\ part\ only\ to\ Germany\ (weight)$


2) Limited / with optional M Driver's Package

The fuel consumption, CO₂ emission and electric power consumption figures are determined according to the European Regulation (EC) 2007/715 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO₂ emissions, the CO₂ values may differ from the values stated here (depending on national legislation).

Further information on official fuel consumption figures and specific CO₂ emission values of new passenger cars is included in the following guideline: 'Leitfaden über den Kraftstoffverbrauch, die CO₂-Emissionen und den Stromverbrauch neuer Personenkraftwagen' (Guide to the fuel economy, CO₂ emissions and electric power consumption of new passenger cars), which can be obtained free of charge from all dealerships, from Deutsche Automobil Treuhand GmbH (DAT), Hellmuth-Hirth-Str. 1, 73760 Ostfildern-Scharnhausen and at https://www.dat.de/co2/.

BMW M4 Competition Coupé. Ouput and torque diagrams.



BMW M4 Competition Coupé. Exterior and interior dimensions.

